



Model Number

IUZ-HH41/43-CHARGER-US

Charger for IUT-HH41* and IUT-HH43*

Function

This charger can be used to connect handheld IUT-HH41-* and IUT-HH43-* to a PC via USB or Ethernet. The charger charges a handheld with an inserted battery as well as a spare battery.

Matching system components

IUZ-HH41/43-BAT

Lithium-ion battery for IUT-HH41-* and IUT-HH43-*

IUT-HH41-FR1-01

UHF handheld, Europe

IUT-HH41-FR2-02

UHF handheld, USA

IUT-HH41-FR2-03

UHF handheld, China

IUT-HH43-FR1-01

UHF handheld, Europe

IUT-HH43-FR2-02

UHF handheld, USA

IUT-HH43-FR2-09

UHF handheld, South Korea

Technical data

Output

Output rated operating current	1.25 A (from power supply)
Output voltage	24 V DC (from power supply)

Ambient conditions

Ambient temperature	-20 ... 55 °C (-4 ... 131 °F)
Storage temperature	-20 ... 60 °C (-4 ... 140 °F)

Mechanical specifications

Connection	USB (type Mini-B) and LAN (RJ45)
Mass	370 g
Dimensions	105 mm x 168 mm x 140 mm
Note	Option to charge a spare battery available Power supply (Type A for USA) and USB cable included in the scope of delivery